Visit **www.brpaper.com** for downloading previous years question papers of 10th and 12th (PSEB and CBSE), B-Tech, Diploma, BBA, BCA, MBA, MCA, M-Tech, PGDCA, B-Com, BSC-IT, MSC-IT.

Roll No.					Total No. of Pages: 02

Total No. of Questions: 09

B.Tech.(CE) (2011 Onwards) (Sem.-3)
FLUID MECHANICS-I
Subject Code: BTCE-301

Paper ID: [A1113]

Time: 3 Hrs. Max. Marks: 60

INSTRUCTION TO CANDIDATES:

- SECTION-A is COMPULSORY consisting of TEN questions carrying TWO marks each.
- 2. SECTION-B contains FIVE questions carrying FIVE marks each and students have to attempt any FOUR questions.
- 3. SECTION-C contains THREE questions carrying TEN marks each and students have to attempt any TWO questions.

SECTION-A

1) Write briefly:

- a) Define surface tension.
- b) Calculate the height of water column corresponding to a pressure equivalent of 75 cm of mercury column.
- c) Calculate the depth of centre of pressure in a rectangular lamina immersed vertically in water upto height *h*.
- d) Define streamline.
- e) Define kinetic energy correction factor.
- f) Define repeating variables.
- g) State true or false for the following sentence. If false, write the correct statement. "In river models, Froude model law is the basic similitude criterion".
- h) Draw the graph between coefficient of drag and reynolds number for a sphere.
- i) What is the function of a pitot tube?
- i) State the momentum equation.

1 M-56072 (S2)-551

SECTION-B

- 2) Check whether the flow defined by the stream function $\psi = 2xy$ is irrotational? If so, determine the corresponding velocity potential.
- 3) How is the drag and lift forces caused on a body immersed in a moving fluid?
- 4) State the principle of pressure measurement by manometer. Explain the difference between a simple and a differential manometer.
- 5) A 30 cm diameter pipe carries water under a head of 20 metres with a velocity of 3.5 *m/sec*. If the axis of the pipe turns through 45°, find the magnitude and direction of the resultant force on the bend.
- 6) In 1 in 20 model of stilling basin, the height of hydraulic jump in the model is observed to be 20 *cm*. What would be the corresponding height of jump in the prototype? If energy dissipation in the model is 0.1 *kW*, what would be the corresponding value in the prototype?

SECTION-C

- A thin plate of area A is placed midway in a gap of height h between two horizontal plane surfaces. The gap is filled with oil of viscosity μ_1 and the plate is pulled edgewise with a constant velocity v. The gap is next filled with a lighter oil of viscosity μ_2 and the plate is located unsymmetrically in the gap but parallel to the walls. Experiments indicate that for the same velocity v the force required was same. Establish a relation for μ_2 in terms of μ_1 and the distance from the near wall to the plate.
- 8) A square door with side dimensions 30 cm is provided in the side wall of a tank which is filled with water of specific weight 9790 N/m^3 . What force must be applied at the lower end of the gate so as to hold the hinged door closed? The hinged end of the door lies at a depth of 3 m from the free water surface. How this force would change if the water is subjected to a pressure of $0.5 \times 10^5 N/m^2$.
- 9) Derive the Euler's equation of motion along a streamline, and hence derive the Bernoulli's theorem.

2 M-56072 (S2)-551